CLEVERTOUCH

The market leading interactive touchscreen



55" Clevertouch Fusion

- Fitted to electronic tilting trolley
- Can be used in three modes: whiteboard, easel, and table
- PC features Intel® Core™ i5 Processor
- In-built PC features
- 32-point touch
- Supplied with Snowflake software
- 3 year on-site de/re installation warranty in the UK

Software suite included:







Annotation software

Collaboration software

Multi-touch software suite



32 point touch



Anti glare glass



112.2kg



Power consumption <220 watts



Integrated speakers 2 x 10W



High Definition



S Durability



Plug and Play

CLEVERTOUCH

The market leading interactive touchscreen

55" Clevertouch Fusion

1544010



| Diagonal size | 55inch |
|-------------------------------------|---------------------|
| Glass type | Anti Glare |
| Panel resolution | 1920 x 1080 |
| Native resolution | 1920 x 1080/60Hz |
| Brightness (nits) | 450 (typical) |
| Contrast ratio | 4000:1 (typical) |
| Response time (grey to grey) | 6.5ms |
| Aspect ratio | 16:9 |
| Display colours | 16.7M |
| Viewing angle horizontal / vertical | 178°/178° |
| Pixel pitch (mm) | 0.63 (w) x 0.21 (h) |
| Back light unit | LED |
| | |

Connectivity

| D-sub, Component, Composite |
|------------------------------------|
| HDMI x2, DVI |
| D-sub |
| HDMI, DVI / VGA 3.5mm mini jack |
| 6 Ohm |
| USB-B |
| 2x USB-A |
| RS485 |
| RS485 |
| |

Features

| Video | Color temp. | 5700(warm), 6500(Warm), 9300(cool), USER |
|----------|-------------------------|--|
| | Progressive scan | ~ |
| Sound | Stereo | ✓ |
| | Output | 10W |
| | Built-in speakers | 10W x 2 |
| Function | Languages | English, Spanish, French, Dutch, Chinese(S), Chinese (T), Japanese. (Able to add new language, option) |
| | Auto ambience detection | ✓ |
| | IPC adaptation | v |

Power

| Service and warranty | 3 years |
|-----------------------------------|--------------|
| Power consumption | < 220 watts |
| Power consumption in standby mode | < 0.75 watts |



Physical Specification

| Dimensions whiteboard mode (mm) | 1286 (w) x 1146-1646 (h) x 725 (d) |
|---------------------------------|------------------------------------|
| Dimensions table mode (mm) | 1286 (w) x 819-1319 (h) x 725 (d) |
| Product weight | 112.2kg |
| Green approvals | Lead free, RoHS compliant |
| Regulatory approvals | CE/FCC |
| Thickness of toughened glass | 4mm |

Touch system

| Detection method | SLW - 32 point |
|-------------------------------|--|
| Touch tool | Stylus, Finger, Solid Object (over 8mm nib) |
| Accuracy | ±2mm |
| Read speed | >100 frame/s |
| Response time | <20ms |
| Effective screen size (w x h) | 1217.6 x 688.4 (mm) |
| Interface | USB-B |
| Supported OS | Windows, MAC, Linux |
| Touch driver for Windows | XP / Vista / 7 / 8 Plug & Play |
| Touch driver for Mac | Lion / Mountain Lion |
| Touch driver for Linux | Ubuntu |

Accessories

| USB cable | ✓ (1.9 metres) |
|----------------------------|----------------|
| Power cable | ✓ (1.7 metres) |
| VGA cable | ✓ (1.4 metres) |
| HDMI cable | ✓ (1.8 metres) |
| Audio cable | ✓ (1.8 metres) |
| Remote control + batteries | V |
| Stylus pen | ✓ |
| Pen tray | ✓ |
| User manual | ✓ |
| Driver disc | Not required |