



Ultra Short Throw Interactive Projector

FEATURES

- Ultra short throw lens to make 100 inch screen at only 44cm away
- 3,300 ANSI lumens of brightness, WXGA resolution, and 10,000:1 contrast ratio for clear, crisp and bright projection
- Built-in interactivity for multi users with 2 pens or optional finger touch
- 2x 10W speakers and microphone input ensure you are clearly heard
- Long lasting life with up to 10,000 hours lamp-life
- Eco Friendly and Energy Saving with sleep timer and also auto-power-off when there is no signal input
- Integrated network monitoring and management solutions including Crestron® RoomView™, Extron, and etc.
- 5 year education warranty
- Compatible with Novo wireless collaboration solution



Ultra short throw lens can make 100 inch projection screen from as little as 44cm away

The D756USTi features WXGA resolution and 3,300 ANSI lumens for clear and sharp projection. It comes with built-in dual-pen interactivity and can be further extended to 10-finger-touch with the optional finger-touch module. The projector is made with eco friendliness in mind with various features including sleep timer and auto-power-off when there is no signal input to be energy conscious. Its 2x10W speakers and microphone input make sure you are clearly heard.



D756USTi SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3300
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	10,000:1
	Keystone Correction	Vertical: +/- 40°
Optical	Throw Ratio	0.35: 1
	Zoom Ratio	Fixed 1x
	Lens Shift (Based on Full Image Height)	Limited Lens Shift Vertical ±1.7%
	Image Size (Diagonal)	80"- 100"
	Projection Distance	283 - 446 mm
	Projection Lens	F = 2.5, f = 5.1 mm
	Offset (Based on Full Image Height)	120%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
	Interactivity	Interactive pens & Optional Finger Touch
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI v1.4 (x2), S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, USB A (Power Only), USB miniB (Interactivity), USB B (Service), Microphone (Mini-Jack), Interactive Function (Interactive pens & Optional Finger Touch)
General	Dimensions (W x D x H)	287.7 x 374.5 x 122.6 mm (not including height of mirror)
	Weight	5
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 250W (Eco. Mode), 290W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	5,000 / 10,000 Hours (Normal / Eco. Mode), 230W/200W
	Speakers	10W x 2
	Noise Level	33dB / 29dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), IR interactive Pen / nbr, AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811118004-SVV), 3D Glasses P/N (3534257700), Universal Wall Mount (T/R 0.35) (3900228200), Remote Control P/N (5041841300), Interactive Pen P/N (5811118885-SVV)
	Warranty	Education Warranty: 5 years projector / 3 years on lamp or 2000 hours whichever comes first
	UPC Code	813097 021861