



Ultra-Short-Throw Projector with Widescreen Projection and a Host of Connectivity Options

FEATURES

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Delivers a large 80" to 100" image from an ultra-short distance
- Helps prevent shadow obstruction and light glare in the presenter's eyes
- 3,300 ANSI lumens with a 10,000:1 contrast ratio
- Powerful 10Wx2 audio speakers make sure you are clearly heard
- Network ready for integration and system administration via RJ45
- High-efficiency lamp that lasts up to 10,000 hours (in economy mode)
- Top-loading, cover for quick and easy lamp replacement



Peace of mind and lower total cost of ownership

With a high brightness of 3,300 ANSI Lumens and a 10,000:1 contrast ratio the D757WT is able to deliver sharp, vibrant pictures. The projector features direct 3D, ensuring that the D757WT is more than capable of handling media applications available now and in the future. The new Dynamic Eco lamp management system, increases the lamp life up to 10,000 hours, which makes the D757WT an economic projector to run.



D757WT SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3300
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920x1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	10,000:1
	Keystone Correction	Vertical: +/- 40°
Optical	Throw Ratio	0.35:1
	Zoom Ratio	Fixed 1x
	Lens Shift (Based on Full Image Height)	Limited Lens Shift Vertical ±1.7%
	Image Size (Diagonal)	80"- 100"
	Projection Distance	283 - 446 mm
	Projection Lens	F = 2.5, f = 5.1 mm
	Offset (Based on Full Image Height)	120%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI v 1.4 (x2), S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, 3D-Sync, USB A (Power Only), USB B (Service), Microphone (Mini-Jack)
General	Dimensions (W x D x H)	287.7 x 374.5 x 122.6 mm (not including height of mirror)
	Weight	5
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 250W (Eco. Mode), 290W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	5,000 / 10,000 Hours (Normal / Eco. Mode), 230W/200W
	Speakers	10W x 2
	Noise Level	33dB / 29dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811118004-SVV), 3D Glasses P/N (3534257700), Optional Wall Mount (%WM-3), Remote Control P/N (5041841300)
	Warranty	Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	UPC Code	813097023483